



MS. JOLIE

DP2 FAST CREW SUPPLY VESSEL



VESSEL DETAILS

Year Built 2014
Official Number 1250539
Place Built Breaux Brothers, Loreauville, La

DIMENSIONS

Length 205 Ft
Beam 32 Ft
Length On Deck 140 Ft
Cargo Length, On Deck 40 Ft
Depth 14 Ft 6 In
Dead Weight 510 Long Tons
Deck Cargo 420 Long Tons
Clear Deck 140 Ft X 26 Ft 6 In
(3710 Sq Ft Inside Cargo Rails)
Gross Tonnage 97

LIQUID CAPACITIES

Ship Water 900 Gals.
Potable Water 42,306 Gals.
Fuel 66,145 Gals.
Lube Oil 1,040 Gals. (2 tanks)
Waste Oil/Bilge Oil 1,050 Gals. (2 tanks)

MACHINERY

Main Engines: 4 – 3512C Caterpillar (1911 Bhp Each @ 1600 Rpm with Zf W7600 2:47:1 Marine Gear Turning 56" X 56" ZF Props)

Generators: 2 – Cat C9 80 K.w. W/Bow Thruster Pump On Front End

Bow Thrusters: 2 – Thrustmaster 30" Od Tunnel Thrusters, Model 30TT200AL

Speed: Lightship 28 Knots
Loaded (180 Tons Cargo) 26 Knots
Loaded (240 Tons Cargo) 24 Knots

Steering & Controls: 4 – Beier, Inc. 5Hp Electro/Hydraulic Steering Units, 3 Stations, Mathers Clear Command Electronic Controls, 3 Stations

DP SYSTEM

Beier IVCS 2000 Dp2 Integrated Vessel Control System

FIFI – 2 6000 GPM FIRE MONITORS*

OIL DISPERSANT SYSTEM

DP2 Beier IVCS 2000
USCG Safety Standby Certified
4 - 25 Man Inflatable Life Rafts
EEP Certified for 86 Persons

* Available for activation upon request.

ELECTRONICS

1 Kvh V7 Marine Rapid-Sat Maritime Broadband System with Unlimited Voice, Internet And Email

2 VHF Radios
1 SSB Radio
2 Radars

GPS
Depth Recorder
Navtex Receiver
Color Video Sounder
EPIRB
AIS
Loud Hailer

ACCOMODATIONS

14 Berths

CERTIFICATIONS

USCG Licensed And Approved For 54 Passengers, (24 VIP Reclining, 30 Standard)
ABS Load Line Certified
+A1 Class, +AMS, HSC
USCG SAFETY STANDBY CERTIFIED
EEP Certified for 86 Persons

ADDITIONAL EQUIPMENT

Personnel Rescue Davit
Fire Detection System
Alarm Monitoring System
Co2 Fire Suppression System
4 – 25 Man Inflatable Life Rafts
Oil Dispersant System (300 GMP - 1,000 gallon and additional on-deck capabilities, 96' boom spray)
Fire Monitor 2 - 6000 GPM